



Product Data

6x5" Column Speaker

Series: LABSTREAK
Model: LABSTREAK p (passive)

Dimensions H 1160 x W 150 x D 225 mm
Local Box H - x W - x D mm
Export Box H - x W - x D - mm
Net weight 19,5 kg
Export boxed - kg

Power Handling (RMS/Program)	LF 500/1000 W HF 240/1000 W
Nominal Impedance	3,3 Ohm
Frequency Range (-10dB)	58 Hz - 35 kHz
Crossover Frequency	1200 Hz
Directivity horizontal	90° / 120° optional mechanical adjustment)
Directivity vertical	8° / up to 18° F.I.R. beam steering
Maximum Output	LF 133dB @ 1000 W HF 150dB @ 1000 W
Low Frequency Driver Chassis type	6 x ultra low distortion low midrange driver
Low Frequency Driver Magnet	Neodymium
Low Frequency Driver Chassis diameter	5" / 128 mm
Low Frequency Driver Voicecoil diameter	1,5" / 38 mm
High Frequency Driver Chassis type	3 x planar wave driver
High Frequency Driver Magnet	Neodymium
High Frequency Driver Chassis diameter	4" x 1" / 101,6 x 25,4 mm
High Frequency Driver Voicecoil diameter	1,75" / 44,4 mm